
AUTOMOTIVE APPLICATION PROFILE

Idler Pulley

We understand that in the automotive industry, you need reliable materials that perform to a higher standard. Ascend offers a comprehensive portfolio of engineered plastics for challenging automotive applications. We work with our customers to achieve the very best from our products. That's why we offer a worldwide support network of application specialists and technical experts. Our material knowledge and expertise in automotive systems can help you improve part performance and reduce material usage and cycle times.

Products Used: R530H, R535H, R540H, R550H

Application Description

Pulleys are a critical component in the accessory belt drive system. The stiffness, dimensional stability and temperature resistance are critical in maintaining optimum performance of the system. A smooth surface is needed to minimize the wear on the drive belt. Also, the chemical resistance of the PA66 eliminates problems with typical automotive chemicals.

Benefits

- Stiffness
- Shear strength
- Wear resistance
- Longer belt life
- Smooth surface
- Dimensional stability
- Temperature resistance
- Chemical resistance

The Vydyne Difference

Ascend's Vydyne[®] nylon 6,6 is ideal for this application because of its superior stiffness, shear strength and performance at elevated temperatures. The smooth surface provides for optimum belt life and performance. Vydyne PA66 resins can be more cost effective than competing resin systems.

Metal Replacement

Vydyne R550H is an excellent alternative to metal because of its high tensile strength, light weight and corrosion resistance. Idler and tensioner pulleys made with PA66 are lighter, lowering rotating inertia and increasing belt life. The lower inertia, smooth surface and high wear resistance reduce noise, vibration and harshness (NVH).



Product Properties



R530H, R535H, R540H, R550H						
Property*	Test Method	Units	R530H	R535H	R540H	R550H
Density	ISO 1183	g/cm ³	1.37	1.41	1.46	1.58
Tensile Strength	ISO 527-2	MPa	195	210	220	240
Flexural Modulus	ISO 178	MPa	9,600	10,500	12,300	16,000
Notched Izod	ISO 180	kJ/m ²	11	12	14	17
DTUL @ 1.8 MPa	ISO 75-2/A	°C	250	250	252	255

*Dry as molded (DAM)

Application Development and Support

Our automotive applications team relies on years of industry experience and CAE support for tooling to help you optimize your system design. For more information, contact our expert applications specialists or visit ascendmaterials.com.



Ascend Performance Materials is the world's largest fully integrated producer of nylon 6,6 resin. We manufacture and reliably supply world-class plastics, fibers and chemicals that are used in thousands of everyday applications such as car parts, electronics and cable ties.

North America

1010 Travis Street
Suite 900
Houston, TX 77002
United States
+1 713 315 5700

Europe

Watson & Crick Hill Park
Rue Granbonpré 11 – Bâtiment H
B-1435 Mont-Saint-Guibert
Belgium
+32 10 608 600

Asia

Unit 3602,
Raffles City Office Towers
268 Xi Zang Road (M)
Shanghai 200001
China
+86 21 2315 0888

© 2018 Ascend Performance Materials Operations LLC. The Ascend Performance Materials and Vydyne marks and logos are trademarks or registered trademarks of Ascend Performance Materials Operations LLC.

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, Ascend Performance Materials Operations LLC makes no representations or warranties as to the completeness or accuracy thereof. The full disclaimer of warranty and liability can be found at ascendmaterials.com/disclaimer. Rev. 10/2018 AAP015

inspiring everyday